



## DECLARATION OF PERFORMANCE

Nº. DoP: 02

### 1. Product **KOBERT-IN FR**

A panel with a nominal thickness of 4 mm, composed of a 3.4 mm thick polyethylene core with mineral fillers, coated on the front and back with 0.3 mm aluminum sheets (ACP).

Kobert-In FR is available in the following finishes: *Sabbia, Specchio, and Ultramatt.*

### 2. Name and address

**BARNIZADOS INDUSTRIALES S.A.**  
Calle Cuarte Norte, 22  
Santa Bárbara -Tarragona  
SPAIN

**3. Use provided** Wallcovering panels for internal use in buildings

**4. Evaluation of system** System AVCP 3

**5. Technical specifications harmonized** EN 17104:2021

### 6. Notified body

Notified body	Nº. NB	Test report	Date
AIDIMME	1981	251.I.1806.061.ES.01	June 6 <sup>th</sup> , 2018
AIDIMME	1981	251.C.1806.061.ES.01	June 6 <sup>th</sup> , 2018
Normec Product Testing	2695	SPT2022-R122	May 17 <sup>th</sup> , 2022
Normec Product Testing	2695	SPT2022-R290	December 30 <sup>th</sup> , 2022



## DECLARATION OF PERFORMANCE

Nº. DoP: 02

### 7. Performance declarations

Essential characteristics	Performance
Reaction to fire	B-s1,d0
VOC emission <i>Spechio y Ultramatt Sabbia</i>	0,04 mg/m <sup>3</sup> 0,5 mg/m <sup>3</sup>
Emission of formaldehyde	E1
Migration of heavy metals  Antimony (Sb) Barium (Ba) Selenium (Se)	0,040 mg/kg conforming conforming
Impact resistance	E <sub>50</sub> > 15 J
Sound absorption  <i>Spechio y Ultramatt Sabbia</i>	<i>a<sub>p</sub></i> = 0,05 <i>a<sub>p</sub></i> = 0,1
Thermal resistance	0,01 m <sup>2</sup> ·K/W

- The performance of the product identified in item 1 are in conformity with the declared performance in item 7.
- This declaration of performance is issued under the sole responsibility of the manufacturer indicated in item 2.
- Signed for and on behalf of the manufacturer by: Carlos Sabaté Balsells

Tarragona, March 6<sup>th</sup>, 2023

**BARINSA**  
BARNIZADOS INDUSTRIALES, S.A.  
CIF A-43098383  
Cuartel Norte, 22  
Tel. 977 71 80 00 - Fax 977 62 61  
43570 SANTA BARBARA (Tarragona)

